



The Thin LCD 515 and 517 feature the integration of bright 15" and 17" LCD displays, respectively, over an efficient and powerful VIA x86 1.5GHz powered thin client platform, with optional Infra-red touch screen, internal wireless communication, and magnetic stripe reader.

The full featured yet elegant, space-saving package accommodates a range of accessories and peripherals to support a wide variety of vertical applications. The software operating systems support server- and browser based computing in addition to local, embedded applications.

The versatility in hardware and software makes the device compelling for numerous vertical deployments leveraging network access and custom software .

Key Features

- Elegant all-in-one, slim, space-saving design
- Fanless, high-performance operation
- High contrast LCD panel with wide viewing angle
- Low power consumption
- IR touch screen
- VESA-mountable for flexibility in mounting and deployment
- Integrated 802.11 a,b,g wireless LAN
- Comprehensive software for remote monitoring, control, and upgrade
- Optional magnetic card reader, bar code scanner and presence sensor module

Applications

The Thin LCD 515 and 517 is ideal for the following applications:

- Kiosk
- Retail
- Entertainment / Gaming
- Education
- Manufacturing
- Hospitality
- Control and Monitoring
- Finance
- Healthcare

Highlights

- **High-integration and energy-efficient processor technology**
- **Fanless construction for quiet and reliable operation**
- **15" and 17" TFT displays, VESA mountable**

Standard Package

- **One (1) Thin LCD 515 or Thin LCD 517**
- **AC / DC adapter with power cord**
- **Keyboard and mouse**
- **Documentation**

Call 1.888.TANGENT

www.tangent.com



Adjustable POS Countertop Mount (11" -15")



Adjustable POS Through-Counter Mount (11" -15")



Compact POS Countertop Mount



Wall Mount with 4" extension arm

Specifications

Operating System

Microsoft® Windows® XP Embedded or XP Professional

Processor

VIA x86 1.5 GHz

Memory

1GB

Display

15" TFT LCD or 17" TFT LCD IR Touch Screen
 LCD 515: 1024x768 (XGA) LCD 517: 1280x1024 (SXGA)

Storage System

Internal flash module 2GB, External USB
 Optional: 120GB SATA HDD

Network Interface

10/100 Ethernet

Wireless LAN

802.11a,b,g wireless LAN

Audio

Built-in Speakers

Operating Conditions

Temperature 0° - 40°C
 Humidity 0% - 90% non-condensing

Power

Input: 100-240VAC Output: 18.5VDC, 3.5A

Display Enclosure

ABS + PC Plastic

I/O Ports:

18.5V DC-in jack
 mic-in, audio-out jack
 Four USB 2.0 ports
 One Serial port
 One RJ45

Base or Pedestal

Detachable aluminum construction;
 VESA-compliant mounting

Dimensions / Weight

LCD 515: 13.9" H x 10.92" W x 2.5" D (w/o stand)
 LCD 517: 16.3" H x 12.6" W x 2.7" D (w/o stand)

LCD 515: 13.9" H x 14" W x 6.7" D (w/stand)
 LCD 517: 15.3" H x 16.1" W x 6.7" D (w/stand)

LCD 515: 13.2 lb LCD 517: 15.4 lb (w/stand)
 LCD 515: 10.6 lb LCD 517: 12.8 lb (w/o stand)

Certification

FCC Class B, CE, UL, C-Tick, RoHS compliant

Limited Warranty

1-year parts & labor, return to depot

Call 1.888.TANGENT

www.tangent.com