

Thin Client 166

Tangent offers a comprehensive line of networkready information appliances, enabling secure and reliable access to the Internet and applications anytime, anywhere. Thin Client 166's efficient design makes it easy to integrate with other devices and mount almost anywhere; on a display, under a desk, or on a mobile cart.



The Product

Thin Client 166 features the integration of the energy efficient, powerful AMD Geode™ GX533 and LX800 processor technology into a small and robust enclosure. The space-saving package supports Microsoft Windows CE and Windows XP Embedded operating systems, accommodating a variety of accessories and peripherals for many vertical needs. Thin Client 166 options include internal wireless and VESA compliant mounting, making it perfect for cable-free and space-constrained applications. With durable, fanless construction, Thin Client 166 provides quiet and dependable operation and a long computing life, lowering the total cost of ownership.

Features

- Support for Windows CE and Windows XP Embedded
- Integrates major thin client/server computing protocols (Citrix ICA, Microsoft RDP), terminal emulation suite; and web browsers
- Comprehensive, easy remote device administration through server-based software
- Small form factor for space-saving, desktop and mounted deployments
- Fanless, flash memory-based with no moving parts
- Custom bracket for VESA compliant mounting to LCD displays and VESA mounts
- Available options for wireless networking; USB-to-Serial and USB-to-PS/2 ports

Applications

Thin Client 166 has many applications, including:

- Inventory and Warehousing
- Manufacturing
- Finance
- Control and Monitoring
- Education
- Healthcare
- Retail
- Hospitality

Highlights

- High-integration and energy-efficient processor technology
- Robust and fanless construction for quiet and reliable operation
- Low-cost computing in compact and versatile packaging


Standard Package & Accessories

- One (1) Thin Client 166
- AC / DC adapter
- Stand for vertical placement
- Documentation

Call 1.888.TANGENT

www.tangent.com

Major Options



- Internal 802.11 wireless adapter (LX only)
- External bracket for mounting to VESA adapters and LCD monitors
- USB-to-Serial and USB-to-PS/2 adapters
- Short VGA cable for connection to mounted display

Specifications

Processor	AMD Geode™ GX 533 or AMD Geode™ LX 800
Display Resolutions	Up to 1600 x 1200 (GX) UP to 1920 x 1440 (LX)
Memory (flash)	64MB-8GB
Memory (RAM)	128MB-256MB (GX) 128MB-1GB (LX)
Operating Systems	Windows CE; Windows XP Embedded
Storage	Internal flash module, External USB
Enclosure	Aluminum chassis; ABS plastic end-caps
Control Buttons	One (1) front Power button
Input / Output Ports	12V DC-in jack; microphone-in; audio-out jack Four (4) USB 1.1 (GX) or USB 2.0 (LX) ports 10/100 BaseT Ethernet VGA
AC / DC Adapter	Input: 100-240 VAC Output: 12VDC
Power Cords	North America, EU, UK
Dimensions (H x W x D)	1.4" x 5.5" x 5.1"
Base Weight	0.88 lb
Regulatory	FCC Class B, CE, UL, RoHS compliant
Operating Temperature	0° - 40°C
Humidity	0% - 90% non-condensing

Call 1.888.TANGENT

www.tangent.com