

CL21

Technical Specifications

Features

- High Brightness Display
- Fanless Design
- Optional DICOM Support
- Antimicrobial Enclosure
- 60601-1-2 4th Edition Compliant
- IP65 Rating Front and Sides
- Optional Anti-Glare Film



Specifications

Display

LCD Size	21.5" (16:9)
Max Resolution	1920 x 1080
Brightness (cd/m ²)	250cd/m ² (Standard Model) 350cd/m ² (DICOM Model)
Contrast Ratio	3000:1 (typ.)
LCD Color	16.7 million
Viewing Angle (H-V)	178° (H) / 178° (V)
Response Time	18ms (typ.)
Backlight MTBF	30,000 hours

Touch

Touch Screen	Projected capacitive w/10 points
--------------	----------------------------------

Other Features

Cooling Method	Fanless
Internal Speaker	Yes
OSD Buttons	Yes

I/O

DVI	1 x DVI-D
HDMI	1 x HDMI 1.4A
DisplayPort	1 x DP
USB	1 x USB 2.0 (Type B for Touch Screen uplink)
Others	1 x Power Switch 5 x Function Buttons

Power

Power Input Voltage	12VDC
Power Connector	Barrel Plug 5.5mm (OD) x 2.5mm (ID) w/locking collar
Power Adapter	External Power Adapter, 12V @ 5.0A

Environment

Operating Temp.	32°F to 104°F (0°C to 40°C)
Storage Temp.	-4°F to 140°F (-20°C to 60°C)
Relative Humidity	10% to 90% non-condensing

IP Level	IP65 front panel IPX1 enclosure
Vibration	Operating 5~17 Hz, Amplitude: 0.1 17~500Hz, Acceleration: 1.0G
Shock	Operating: 15g/0.53 oz, 11ms, half sine wave
Certification	<ul style="list-style-type: none"> • CE • FCC • VCCI Class B • IEC60601-1—2 4th Edition

Physical

Enclosure Materials	ABC + PC plastics, antimicrobial enclosure
Dimensions (W x H x D)	21.26" x 14.76" x 3.07" (540mm x 375mm x 78mm)
Weight	14.1lb (6.4Kg)
Mounting	VESA 75 & 100, Optional Stand

Warranty

Warranty	<ul style="list-style-type: none"> • 1-year standard
----------	---