

# Medix M24T

tangent

## FEATURES

- Intel 7<sup>th</sup> Gen. vPro Core i7/i5 Processors
- 2 x 260-pin DDR4 SO-DIMM, up to 32GB
- High Performance NVMe Storage
- Antimicrobial Enclosure
- Fanless Construction w/ Heat Pipes
- TPM
- Optional UPS Battery Backup
- Optional vPro
- Optional Single Sign-on RFID (Integrated)



## SPECIFICATIONS

### Display

LCD Size	23.8" (16:9)
Max Resolution	1920 x 1080 (WUXGA)

### Touch

Touch Screen	Projected capacitive w/ 10 points
--------------	-----------------------------------

### System

Processor	Intel 7 <sup>th</sup> Gen. Core i7/i5 Processors
System Chipset	Intel H110
Graphics Controller	Intel HD Graphics 530 (Core CPU)
LAN Chipset	1 x GbE: Intel I219-V 1 x GbE: Realtek RTL8111
Audio	Realtek ALC283
System Memory	Up to 32GB DDR4 2133/2400 (2 x SO-DIMM)
BIOS	Insyde 64Mbit
TPM	TPM 2.0
vPro	Yes (Optional)

### Storage

NVMe	1 x M.2 2280 "M" Key (PCIe x 4)
------	---------------------------------

### Expansion

M.2	1 x M.2 (M key) supports M.2 2280 1 x M.2 (E key) supports M.2 2230
-----	--

### Other Features

Cooling Method	Fanless w/ heat pipes
Internal Speaker	2 x 1W speakers
WebCam	1 x 2Mpixel camera (optional)

### I/O

Video	1 x HDMI
COM	3 x DB9 serial RS232
USB	4 x USB 3.0 (rear) 2 x USB 2.0 (rear)
LAN	2 x GbE RJ45
WLAN	802.11 AC + BT 4.2 LE
Audio	1 x line-out
Others	1 x power switch 4 x function buttons 1 x SSO RFID (optional)

### Operating System

Windows	Windows 7 Pro 32/64bit Windows 10 Pro 64bit
---------	--

### Power

Power Input Voltage	19 VDC
Power Connector	Barrel plug
Battery	1 x Li-ion UPS backup only (optional)
Power Adapter	External power adapter, 19V @ 6.31A

### Environment

Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Relative Humidity	10% to 90% non-condensing
IP Level	IP65 (front panel) IPX1 (back panel)

- |               |   |
|---------------|---|
| Certification | <ul style="list-style-type: none"> <li>• CE</li> <li>• EN 55011: 2009+A1: 2010 Class B</li> <li>• EN-60601-1: 2006</li> <li>• IEC 60601-1-6:20110/AMD1:2013</li> <li>• 1807005-CB</li> <li>• EN 60601-1-2: 2015</li> <li>• EN 61000-3-2: 2014</li> <li>• EN 61000-3-3: 2013</li> <li>• UL/cUL 60601-1</li> <li>• FCC</li> </ul> |
|---------------|---|

### Physical

Enclosure Materials	ABS + Aluminum Alloy, antimicrobial enclosure
Dimension (W x H x D)	22.34" x 13.78" x 1.78" (567.6 x 350.1 x 45.2 mm)
Weight	Without base: 16.4 lb (7.44 kg) With base: 21.8 lb. (9.89 kg)
Mounting	VESA 100, optional stand

### Warranty

Warranty	1-year standard
----------	-----------------